

PU RELEASE AGENT

Technical Data Sheet

Product name: PU Release Agent Creation date: 08/08/2017 Version: 1.0

Replaces: 0.0

1 : General description

Mould release for polyurethanes at room temperature..

2 : Features

- High tenacity on the support, involving only minor migration.
- Gives a very nice surface condition to the parts.

3: Applications

Intended for the moulding of elastomer polyurethanes. It's application increases considerably life-time of the moulds and their parts in elastomer silicone. It isolates them from chemical aggression..

4: Directions

- Apply on a clean and dry mould.
- Apply a thin even layer.
- Allow the solvents to evaporate

A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.

5: Typical product data (without propellant)

Based on silicone and oil.

- | | |
|-------------------------|------------------------|
| • Aspect | : liquid |
| • Colour | : colourless |
| • Operating temperature | : ambient temperatures |



6: Packaging

Aerosol

12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.