

PBTA4631B - Permabond TA4631B

Printed on 10/05/2024
Page n. 1 / 12
Replaced revision:1 (Dated 31/03/2023)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **PBTA4631B**

Product name Permabond TA4631B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses Industrial **Professional** Consumer

Use

1.3. Details of the supplier of the safety data sheet

Permabond Engineering Adhesives

Full address Niederkasseler Lohweg 18 **District and Country** 40547 Düsseldorf

Germany

+44 (0)1962 711 661 Tel.

e-mail address of the competent person responsible for the Safety Data Sheet

info.europe@permabond.com

Supplier: **Permabond Engineering Adhesives Ltd**

Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

> CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

toxicity, category 3

Reproductive toxicity, category 1B H360D May damage the unborn child. Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation. Skin sensitization, category 1 H317 May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. Hazardous to the aquatic environment, chronic H412



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 2 / 12

Page n. 2 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H360DMay damage the unborn child.H319Causes serious eye irritation.H315Causes skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Restricted to professional users.

Precautionary statements:

P202 Do not handle until all safety precautions have been read and understood.

P273 Avoid release to the environment.

P280 Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice / attention.

Contains: TETRAHYDROFURFURYL METHACRYLATE

2-ETHYLHEXYL METHACRYLATE

TRIETHYLBORANE--DIAMINOPROPANE COMPLEX

PROPANE-1,3-DIAMINE

2-DIMETHYLAMINOETHYL METHACRYLATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

TETRAHYDROFURFURYL METHACRYLATE

INDEX $30 \le x < 60$ Repr. 1B H360D, Skin Sens. 1 H317, Aquatic Chronic 3 H412

EC 219-529-5 CAS 2455-24-5

REACH Reg. 1-2120748481-53-XXXX 2-ETHYLHEXYL METHACRYLATE

INDEX 5 \leq x < 10 Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Skin Sens. 1B H317,

Aquatic Chronic 3 H412, EUH208

EC 211-708-6 CAS 688-84-6

REACH Reg. 01-2119490166-35-XXXX



PBTA4631B - Permabond TA4631B

Pated 10/05/2024 Printed on 10/05/2024 Page n. 3 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 3. Composition/information on ingredients

TRIETHYLBORANE--DIAMINOPROPANE COMPLEX

INDEX $1 \le x < 3$ Acute Tox. 4 H312, Skin Corr. 1A H314, Eye Dam. 1 H318, Skin Sens. 1B

H317

EC 604-654-3 ATE Dermal: 1100 mg/kg CAS 148861-07-8

CAS 14886 REACH Reg. Exent

2-DIMETHYLAMINOETHYL METHACRYLATE

INDEX $0.1 \le x < 1$ Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1

H318, Skin Sens. 1 H317

EC 220-688-8 ATE Oral: 500 mg/kg, ATE Dermal: 1100 mg/kg

CAS 2867-47-2

REACH Reg. 01-2119474677-22-XXXX

PROPANE-1,3-DIAMINE

INDEX 0,1 ≤ x < 1 Flam. Liq. 3 H226, Acute Tox. 2 H310, Acute Tox. 4 H302, Skin Corr. 1C

H314, Eye Dam. 1 H318, Resp. Sens. 1 H334, Skin Sens. 1B H317

LD50 Oral: 311 mg/kg, LD50 Dermal: 178 mg/kg

EC 203-702-7 CAS 109-76-2

REACH Reg. 01-2119977065-31-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request

medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Give plenty of water to drink. Do not cause vomiting. Consult a doctor.

Inhalation: Move the exposed person to fresh air. Consult a doctor in case of serious symptoms or

persistent.

Rescuer protection

Information not available

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash.

Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

Means to have available in the workplace for specific and immediate treatment

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 4 / 12 Replaced revision:1 (Dated 31/03/2023)

health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany): 6.1C

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

2-ETHYLHEXYL METHACRYLAT	Έ	
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,003	mg/l
Normal value in marine water	0	mg/l
Normal value for fresh water sediment	2,24	mg/kg
Normal value for marine water sediment	0,224	mg/kg
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,446	mg/kg



PBTA4631B - Permabond TA4631B

Printed on 10/05/2024 Page n. 5 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 8. Exposure controls/personal protection

	/	>	>

TETRAHYDROFURFURYL METHACRYLATE								
Predicted no-effect con	centration	- PNEC						
Normal value in fresh	Normal value in fresh water 0,347 mg/l							
Normal value in marir	ne water					0,035	mg/l	
Normal value for fresh	n water sedi	ment				2,12	mg/kg/d	
Normal value for mari	ne water se	diment				0,212	mg/kg/d	
Normal value of STP	microorgani	sms				15,8	mg/l	
Normal value for the t	errestrial co	mpartment				0,221	mg/kg/d	
Health - Derived no-effect level - DNEL / DMEL								
	Effects or	n consumers			Effects on	workers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral		•		0.5				-
				mg/kg/d				
Inhalation				0.87				3.53
				mg/m3				mg/m3
Skin				0.5				1
				mg/kg/d				mg/kg/d

		2-DIN	METHYLAMINO	ETHYL METH	ACRYLATE			
Predicted no-effect co	ncentration	- PNEC						
Normal value in fresh	n water					0,087	mg/l	
Normal value for fres	h water sed	iment				0,483	mg/kg	
Normal value of STP	microorgan	isms				210	mg/l	
Normal value for the	terrestrial co	ompartment				0,0454	mg/kg	
lealth - Derived no-eff	ect level - [ONEL / DMEL						
	Effects o	n consumers			Effects on w	orkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					321		27	27
					mg/m3		mg/m3	mg/m3
Skin								41,7
								mg/kg
								bw/d

			PROPAN	NE-1,3-DIAMIN	E			
redicted no-effect co	ncentration	- PNEC						
Normal value in fresh	n water					1	mg/l	
Normal value in mari	ne water					0,1	mg/l	
Normal value for fres	h water sed	iment				5	mg/kg	
Normal value for marine water sediment						0,5	mg/kg	
Normal value of STP				10	mg/l			
lealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects o	n consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation								3
								mg/m3
Skin								0,26
								mg/kg
								bw/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 6 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 8. Exposure controls/personal protection

on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties		Value	Information		
Appearance		liquid			
Colour		transparent			
Odour		characteristic			
Melting point / freezing point		not available			
Initial boiling point		not available			
Flammability		not available			
Lower explosive limit		not available			
Upper explosive limit		not available			
Flash point	>	100 °C			
Auto-ignition temperature		not available			
Decomposition temperature		not available			
pH		not available	Reason for missin	g data:subs	tance/mixture is
			non-soluble	(in	water)
Kinematic viscosity		not available			
Dynamic viscosity		~ 12000 mPa.s	Temperature: 25 °	С	
Solubility		not available			
Partition coefficient: n-octanol/water		not available			
Vapour pressure		not available			
Density and/or relative density		1			
Relative vapour density		not available			
Particle characteristics		not applicable			

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

The following materials may react with the product: Strong oxidizing agents, Reducing agents, strong acids and bases.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



PBTA4631B - Permabond TA4631B

Revision In.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 7 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 10. Stability and reactivity/>>

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Stable under normal conditions of storage and use. Protect from direct sunlight.

Avoid contact with acids and oxidizing agents.

10.5. Incompatible materials

See the reactivity section.

10.6. Hazardous decomposition products

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)
ATE (Oral) of the mixture: Not classified (no significant component)

ATE (Dermal) of the mixture: >2000 mg/kg

2-ETHYLHEXYL METHACRYLATE

LD50 (Dermal): > 17620 mg/kg LD50 (Oral): > 2000 mg/kg

TETRAHYDROFURFURYL METHACRYLATE

LD50 (Oral): 3945 mg/kg

2-DIMETHYLAMINOETHYL METHACRYLATE

LD50 (Dermal): > 2000 mg/kg

ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): > 2000 mg/kg

PROPANE-1,3-DIAMINE

LD50 (Dermal): 178 mg/kg LD50 (Oral): 311 mg/kg

TRIETHYLBORANE--DIAMINOPROPANE COMPLEX



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 8 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 11. Toxicological information/>>

ATE (Dermal):

1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

May damage the unborn child

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

2-ETHYLHEXYL METHACRYLATE

LC50 - for Fish 2,78 mg/l/96h
EC50 - for Crustacea 2,18 mg/l/48h
EC50 - for Algae / Aquatic Plants 7,68 mg/l/72h
Chronic NOEC for Crustacea 0,11 mg/l
Chronic NOEC for Algae / Aquatic Plants 0,28 mg/l

TETRAHYDROFURFURYL METHACRYLATE

 LC50 - for Fish
 34,7 mg/l/96h

 EC50 - for Crustacea
 69 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 > 100 mg/l/72h

 Chronic NOEC for Fish
 9,4 mg/l

 Chronic NOEC for Crustacea
 37,2 mg/l

2-DIMETHYLAMINOETHYL METHACRYLATE

 LC50 - for Fish
 19,1 mg/l/96h

 EC50 - for Crustacea
 33 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 69,7 mg/l/72h





PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 9 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 12. Ecological information .../>>

Chronic NOEC for Crustacea
Chronic NOEC for Algae / Aquatic Plants

4,35 mg/l 32 mg/l

12.2. Persistence and degradability

TETRAHYDROFURFURYL METHACRYLATE NOT rapidly degradable

2-DIMETHYLAMINOETHYL METHACRYLATE Rapidly degradable

12.3. Bioaccumulative potential

TETRAHYDROFURFURYL METHACRYLATE

Partition coefficient: n-octanol/water

1,38 Log Kow

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste class 08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 10 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 14. Transport information .../>>

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: No

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3	Flammable liquid, category 3
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C

ΕN



Permabond Engineering Adhesives

PBTA4631B - Permabond TA4631B

Printed on 10/05/2024 Page n. 11 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 16. Other information .../>>

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Resp. Sens. 1 Respiratory sensitization, category 1 Skin Sens. 1 Skin sensitization, category 1 Skin Sens. 1B Skin sensitization, category 1B

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H226 Flammable liquid and vapour. H360D May damage the unborn child. H310 Fatal in contact with skin. H302 Harmful if swallowed. Harmful in contact with skin. H312

Causes severe skin burns and eye damage. H314

Causes serious eye irritation. H319 H315 Causes skin irritation. H335

May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains <name of sensitising substance>. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)



PBTA4631B - Permabond TA4631B

Revision nr.2 Dated 10/05/2024 Printed on 10/05/2024 Page n. 12 / 12 Replaced revision:1 (Dated 31/03/2023)

SECTION 16. Other information .../>>

- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 04 / 11 / 13 / 14 / 15.