

Permabond TA4660B

Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 1 / 13

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Permabond TA4660B Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Adhesive**

Identified Uses Industrial **Professional** Consumer Use

1.3. Details of the supplier of the safety data sheet

Name **Permabond Engineering Adhesives** Niederkasseler Lohweg 18 Full address **District and Country** 40547 Düsseldorf Germany Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet

info.europe@permabond.com

Supplier: **Permabond Engineering Adhesives Ltd**

> Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

> CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Specific target organ toxicity - single exposure,	H335	May cause respiratory irritation.
category 3		
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic	H412	Harmful to aquatic life with long lasting effects.
toxicity, category 3		



Permabond Engineering Adhesives

Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 2 / 13

SECTION 2. Hazards identification .../>>

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing / eye protection / face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Contains: Trifluoroactic acid

METHACRYLIC ACID

2-HYDROXYETHYL METHACRYLATE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

2-HYDROXYETHYL METHACRYLATE

INDEX 10 ≤ x < 30 Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317

EC 212-782-2 CAS 868-77-9

REACH Reg. 01-2119490169-29-XXXX

Trifluoroactic acid

INDEX $5 \le x < 10$ Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, Aquatic Chronic 3

H412

EC 200-929-3 STA Inhalation mists/powders: 1,5 mg/l, STA Inhalation vapours: 11 mg/l

CAS 76-05-1

REACH Reg. 01-2119548396-29-XXXX

METHACRYLIC ACID

INDEX 607-088-00-5 3 ≤ x < 5 Acute Tox. 3 H311, Acute Tox. 4 H302, Acute Tox. 4 H332, Skin Corr. 1A

H314, Eye Dam. 1 H318, STOT SE 3 H335, Classification note according to

Annex VI to the CLP Regulation: D

EC 201-204-4 STOT SE 3 H335: ≥ 1%

CAS 79-41-4 LD50 Oral: 1320 mg/kg, LD50 Dermal: 750 mg/kg, STA Inhalation vapours:

11 mg/l



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 3 / 13

SECTION 3. Composition/information on ingredients/

REACH Reg. 01-2120741502-64-XXXX 2,6-DI-TERT-BUTYL-P-CRESOL

INDEX $1 \le x < 2.5$ Aquatic Chronic 1 H410 M=1

EC 204-881-4 CAS 128-37-0

REACH Reg. 01-2119480433-40-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Skin: Wash the skin thoroughly with soap and water. If symptoms arise, request

medical assistance

Eyes: Make sure you have removed any contact lenses before rinsing your eyes. Wash

Readyly and abundantly the eyes with water keeping the eyelids open.

Continue to rinse for at least 15 minutes. Consult a doctor if the discomfort continues.

Ingestion: rinse the mouth with water thoroughly. Make a abundant quantity of water drink.

Do not cause vomiting. Consult a doctor.

Inhalation: move the subject exposed in the open air. Consult a doctor in case of serious symptoms or

persistent.

4.2. Most important symptoms and effects, both acute and delayed

Contact with the skin: skin irritation. Mild dermatitis, allergic rash. Contact with eyes: irritating and can cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Note for the doctor no specific recommendation. Symptomatic treatment.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS DUE TO EXPOSURE IN THE EVENT OF FIRE

Avoid breathing combustion products, carbon monoxide (CO), carbon dioxide (CO2), and nitric oxides (NOx).

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 4 / 13

SECTION 6. Accidental release measures/>

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Adhesive

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 5 / 13

SECTION 8. Exposure controls/personal protection .../

			2	,6-DI-TERT-B	UTYL-P-CRES	OL			
hreshold Limit Valu	ue								
Type (Country	TWA/8h		STEL/15	min	Remarks / Obs	ervations		
	-	mg/m3	ppm	mg/m3	ppm				
AGW [DEU	10		40					
TLV [NK	10		20					
VLA E	ESP	10							
VLEP F	FRA	10							
HTP F	IN	10		20					
redicted no-effect	concentrat	ion - PNEC							
Normal value in fre	esh water						0,0002	mg/l	
Normal value for fresh water sediment 0,458 mg/kg/d									
Normal value for n	narine wate	r sediment					0,046	mg/kg/d	
Normal value for n	narine wate	r, intermitte	nt release				0,002	mg/l	
Normal value of S	TP microor	ganisms					0,017	mg/l	
Normal value for the	ne food cha	in (seconda	ry poisoning)			16,67	mg/kg	
Normal value for the	ne terrestria	al compartm	ent				0,054	mg/kg/d	
ealth - Derived no-	effect leve	I - DNEL / D	MEL						
	Effec	ts on consur	mers			Effects on worke	rs		
Route of exposure	Acute	e Acut	te	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	syst	emic	local	systemic	local	systemic	local	systemic
Oral		1			0,25				
		mg/l	kg bw/d		mg/kg bw/d				
Inhalation		3,1			0,78		18		4,4
		mg/r	m3		mg/m3		mg/m3		mg/m3
Skin		6,7			1,7		19		4,7
		mg/l	kg bw/d		mg/kg bw/d		mg/kg		mg/kg
							bw/d		bw/d

			2-l	HYDROXYETH'	YL METHACE	RYLATE			
hreshold Limit Valu	ue								
Type (Country	Country TWA/8h STEL/15min		min	Remarks /	Observations			
	-	mg/m3	ppm	mg/m3	ppm				
TLV N	NOR	11	2	11	2				
redicted no-effect	concentrati	on - PNEC	3						
Normal value in fre	esh water						0,482	mg/l	
Normal value in m	arine water						0,0482	mg/l	
Normal value for fresh water sediment 3,79 mg/kg									
Normal value for marine water sediment 3,79 mg/kg									
Normal value for fresh water, intermittent release 1 mg/l									
Normal value of S	TP microorg	anisms				10	mg/l		
Normal value for the terrestrial compartment							0,476	mg/kg	
lealth - Derived no-	effect level	- DNEL / I	DMEL						
	Effects	s on consu	ımers		Effects on workers		orkers		
Route of exposure	e Acute	Acu	ıte	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	sys	temic	local	systemic	local	systemic	local	systemic
Oral					0.83				0.83
					mg/kg/d				mg/kg/d
Inhalation					2.9				4.9
					mg/m3				mg/m3
Skin					0.83				1.3
					mg/kg/d				mg/kg/d



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 6 / 13

SECTION 8. Exposure controls/personal protection .../

				METHA	CRYLIC ACID				
hreshold Limit	t Value								
Туре	Country	TWA/8h		STEL/15	min	Remarks	/ Observations		
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	180	50	360	100				
TLV	DNK	70	20						
VLA	ESP	72	20						
VLEP	FRA	70	20						
HTP	FIN	71	20						
RV	LVA	10							
TLV	NOR	70	20						
TLV	ROU	30	8,5						
NGV/KGV	SWE	70	20	100	30				
WEL	GBR	72	20	143	40				
redicted no-ef	fect concent	ration - PNE	С						
Normal value	in fresh wate	r					0,82	mg/l	
Normal value	in marine wa	ter					0,82	mg/l	
lealth - Derived	d no-effect le	vel - DNEL /	DMEL						
	Effects on consumers				Effects on workers				
Route of expo	osure Ac	ute Ac	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loc	al sys	stemic	local	systemic	local	systemic	local	systemic
Inhalation				6.55	6.3			88	29.6
				mg/m3	mg/m3			mg/m3	mg/m3
Skin					2.55				4.25
					mg/kg bw/d				mg/kg
									bw/d

Trifluoroactic acid		
Predicted no-effect concentration - PNEC		
Normal value in fresh water	0,56	mg/l
Normal value in marine water	0,056	mg/l
Normal value for fresh water sediment	2,36	mg/kg/d
Normal value for marine water sediment	0,236	mg/kg/d
Normal value of STP microorganisms	83,2	mg/l

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 7 / 13

sion nr.1 d 09/05/2023 compilation

SECTION 8. Exposure controls/personal protection/>

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance liquid black Colour Odour characteristic Melting point / freezing point not available Initial boiling point not available Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point 100 °C Auto-ignition temperature not available Decomposition temperature not available not available

Kinematic viscosity not available

Dynamic viscosity ~45000 mPa.s Thixo

Solubility not available
Partition coefficient: n-octanol/water not available
Vapour pressure not available

Density and/or relative density 1

Relative vapour density not available Particle characteristics not applicable Information

Reason for missing data:substance/mixture is non-soluble (in water)

Temperature: 25 °C

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Strong reducing and oxidizing agents.

10.6. Hazardous decomposition products



Permabond Engineering Adhesives

Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 8 / 13

By thermal decomposition, carbon monoxide, carbon dioxide and ed other unidentified organic compounds.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l
ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: >2000 mg/kg

2,6-DI-TERT-BUTYL-P-CRESOL

LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 2930 mg/kg

2-HYDROXYETHYL METHACRYLATE

LD50 (Dermal): > 5000 mg/kg LD50 (Oral): > 5000 mg/kg

METHACRYLIC ACID

 LD50 (Dermal):
 750 mg/kg

 LD50 (Oral):
 1320 mg/kg

 LC50 (Inhalation vapours):
 7,1 mg/l/4h

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

Trifluoroactic acid

STA (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

STA (Inhalation vapours):

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 9 / 13

SECTION 11. Toxicological information .../>>

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

2,6-DI-TERT-BUTYL-P-CRESOL

 LC50 - for Fish
 > 0,57 mg/l/96h

 EC50 - for Crustacea
 0,61 mg/l/48h

 Chronic NOEC for Crustacea
 0,316 mg/l

2-HYDROXYETHYL METHACRYLATE

 LC50 - for Fish
 > 100 mg/l/96h

 EC50 - for Crustacea
 380 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 836 mg/l/72h

METHACRYLIC ACID

 LC50 - for Fish
 85 mg/l/96h

 EC50 - for Crustacea
 > 130 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 45 mg/l/72h

12.2. Persistence and degradability

2,6-DI-TERT-BUTYL-P-CRESOL NOT rapidly degradable

2-HYDROXYETHYL METHACRYLATE

Rapidly degradable

METHACRYLIC ACID Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil



Permabond Engineering Adhesives

Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 10 / 13

SECTION 12. Ecological information/>>

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

08 04 09* stickers and sealed sealing, containing organic solvents or other dangerous substances

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID. IMDG. IATA: 3265

14.2. UN proper shipping name

ADR / RID: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. IMDG: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. IATA: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

@EPY 11.5.1 - SDS 1004.14

ΕN



Permabond Engineering Adhesives

Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 11 / 13

SECTION 14. Transport information .../>>

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80 Limited Quantities: 5 L Tunnel restriction code: (E)

Special provision: 274
IMDG: EMS: F-A, S-B Limited Quantities: 5 L

IATA: Cargo: Maximum quantity: 60 L Packaging instructions: 856
Passengers: Maximum quantity: 5 L Packaging instructions: 852

Special provision: A3, A803

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3
Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 3
Acute toxicity, category 3
Acute Tox. 4
Skin Corr. 1A
Eye Dam. 1
Eye Irrit. 2
Skin Irrit. 2
Skin Irrit. 2
Acute toxicity, category 4
Skin corrosion, category 1A
Serious eye damage, category 1
Eye irritation, category 2
Skin Irrit. 2
Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Skin Sens. 1 Skin sensitization, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3



Permabond Engineering Adhesives

Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 12 / 13

SECTION 16. Other information .../>>

H311 Toxic in contact with skin.
H302 Harmful if swallowed.
H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H335 May cause respiratory irritation.

H335 May cause respiratory irritation.
H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)



Permabond TA4660B

Revision nr.1 Dated 09/05/2023 First compilation Printed on 09/05/2023 Page n. 13 / 13

SECTION 16. Other information .../>>

- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.