

# Permabond 825

Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 1 / 13

# **Safety Data Sheet**

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Permabond 825 Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Adhesive Intended use

1.3. Details of the supplier of the safety data sheet

**Permabond Engineering Adhesives** Name Full address Niederkasseler Lohweg 18

40547 Düsseldorf **District and Country** Germany

+44 (0)1962 711 661 Tel

e-mail address of the competent person info.europe@permabond.com responsible for the Safety Data Sheet

Supplier:

Permabond Engineering Adhesives Ltd Wessex Way, Colden Common,

Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

+44 (0)1962 711 661 ( 8.00 am-5.00 pm Mon-Fri) For urgent inquiries refer to

> CHEMTREC UK: +(44)-870-8200418 CHEMTREC Ireland: +(353)-19014670 CHEMTREC Australia: +(61)-290372994 CHEMTREC New Zealand: +(64)-98010034

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation. Skin irritation, category 2 H315 Causes skin irritation.

Specific target organ toxicity - single exposure, H335 May cause respiratory irritation.

category 3

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 2 / 13

#### SECTION 2. Hazards identification .../>>

Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H335 May cause respiratory irritation.

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

**EUH208** Contains: TERT-BUTYL PERBENZOATE

May produce an allergic reaction.

Precautionary statements:

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 In case of contact with the skin: wash abundantly with soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Contains: ethyl 2-cyanoacrylate

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

### **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

ethyl 2-cyanoacrylate

INDEX 607-236-00-9  $30 \le x < 60$  Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, EUH202

EC 230-391-5 STOT SE 3 H335: ≥ 10% CAS 7085-85-0

REACH Reg. 01-2119527766-29-XXXX

TERT-BUTYL PERBENZOATE

INDEX 0,1 ≤ x < 1 Org. Perox C H242, Acute Tox. 4 H332, Skin Irrit. 2 H315, Skin Sens. 1B

H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412

EC 210-382-2 STA Inhalation mists/powders: 1,5 mg/l, STA Inhalation vapours: 11 mg/l

CAS 614-45-9

REACH Reg. 01-2119513317-46-XXXX

CHLOROBENZENE

INDEX 602-033-00-1 0 ≤ x < 0,1 Flam. Liq. 3 H226, Acute Tox. 4 H332, Skin Irrit. 2 H315, Aquatic Chronic 2

H411

EC 203-628-5 LC50 Inhalation vapours: 15,5 mg/l/4h

CAS 108-90-7

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

Skin: contact with the product, the skin will stick to itself and to anything else immediately. Do not try to remove the contaminated clothing in the product from the skin, because the tight skin can easily tear. Wash the skin thoroughly with

water and soap. Consult a doctor immediately.

Eyes: rinse immediately and abundantly with water. Continue to rinse for

at least 10 minutes. In case of gluing with sticker, do not forcefully separate the eyelids.

Apply a buffer soaked in hot water and allow the eyelids to separate.

Consult a doctor. The money adhesive does not follow the surfaces of the eyes but being

abrasive can cause damage. Consult a doctor immediately.



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 3 / 13

#### SECTION 4. First aid measures .../>>

Ingestion: in contact the product can immediately glue the lips together. Do not cause the

He retched. Consult a doctor.

Inhalation: ventilation of the environment. Bring the subject to the open air, far from the accident site. In case of malaise consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation: nose irritation, throat and airways.

Ingestion: in contact the product can immediately glue the lips together. Skin: prolonged contact with the skin can cause redness and irritation.

Eyes: irritating and can cause redness and pain.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor: in case of glued skin. Slowly separate the skin starting from the edge of the area glued. Help yourself with soap lukewarm water. In case of glued eyes. Do not force the opening of the eyelids. Apply a compress of hot water and let the eyes take they reopen alone.

### **SECTION 5. Firefighting measures**

### 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 4 / 13

## **SECTION 7. Handling and storage**

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Adhesive

### **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

_			_	
Real	ulator	v Ref	ferer	LOGS.

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17
CZE	Česká Republika	Януари 2020г.) Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust.
		17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας
		2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (IÍ. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa
		●FPY 11 4.1 - SDS



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 5 / 13

### SECTION 8. Exposure controls/personal protection

nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení

neskorších predpisov

SVN Slovenija Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)

TUR Türkiye Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik

12.08.2013 / 28733

GBR United Kingdom EH40/2005 Workplace exposure limits (Fourth Edition 2020)

EU OEL EU Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)

2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH ACGIH 2021

				ethyl 2-c	yanoacrylate	)			
Threshold Limit V	alue								
Туре	Country	TWA/8h		STEL/15	STEL/15min		Observations		
		mg/m3	ppm	mg/m3	ppm				
TLV	DNK	10	2	20	4				
VLA	ESP		0,2						
HTP	FIN	1	0,2						
NDS/NDSCh	POL	1		2					
NGV/KGV	SWE	10	2	20	4				
Health - Derived n	o-effect lev	el - DNEL /	DMEL						
Effects on consumers					Effects on wo	orkers			
Route of exposu	ıre Acu	te Acı	ute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loca	ıl sys	temic	local	systemic	local	systemic	local	systemic
Inhalation				9.25	9.25				
				mg/m3	mg/m3				

				CHLOR	OBENZENE	
Threshold Limit V	'alue					
Type	Country	TWA/8h		STEL/15r	min	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	23	5	70	15	
TLV	CZE	25	6,8	70	19,04	
AGW	DEU	23	5	46	10	
MAK	DEU	23	5	46	10	
TLV	DNK	23	5			E
VLA	ESP	23	5	70	15	
TLV	EST	23	5	70	15	SKIN
VLEP	FRA	23	5	70	15	
HTP	FIN	23	5	70	15	SKIN
TLV	GRC	23	5	70	15	
AK	HUN	23		70		
GVI/KGVI	HRV	23	5	70	15	SKIN
VLEP	ITA	23	5	70	15	
RD	LTU	23	5	70	15	
RV	LVA	23	5	70	15	
TLV	NOR	23	5			
TGG	NLD	23		70		
VLE	PRT	23	5	70	15	
NDS/NDSCh	POL	23		70		
TLV	ROU	23	5	70	15	
NGV/KGV	SWE	23	5	70	15	
NPEL	SVK	23	5	70	15	
MV	SVN	23	5	69	15	
ESD	TUR	23	5	70	15	
WEL	GBR	4,7	1	14	3	SKIN
OEL	EU	23	5	70	15	
TLV-ACGIH		46	10			



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 6 / 13

### SECTION 8. Exposure controls/personal protection .../>

			TERT-BUTY	L PERBENZO	ATE			
redicted no-effect cor	ncentration	- PNEC						
Normal value in fresh	water					0,01	mg/l	
Normal value in marii	ne water					0,001	mg/l	
Normal value for fresh water sediment						0,28	mg/kg/d	
Normal value for mar	ine water se	diment				0,028	mg/kg/d	
Normal value of STP	microorgani	sms				0,6	mg/l	
Normal value for the	terrestrial co	mpartment				0,049	mg/kg/d	
ealth - Derived no-eff	ect level - D	NEL / DMEL						
	Effects or	n consumers			Effects on workers			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation					LOW	MED		24,7
								mg/m3
Skin					LOW	NPI	LOW	17,5
								mg/kg
								bw/d

#### Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard; MED = medium hazard; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION** 

Upper explosive limit

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

#### **SECTION 9. Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**Properties** Value Information Appearance liauid Colour colourless Odour pungent Melting point / freezing point not applicable °C Initial boiling point 100 Flammability not available Lower explosive limit not available

not available



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 7 / 13

### SECTION 9. Physical and chemical properties ... / >:

Flash point 83 °C
Auto-ignition temperature not available
Decomposition temperature not available
pH not available

Kinematic viscosity not available

Dynamic viscosity ~ 120 mPa.s

Solubility not available

Partition coefficient: n-octanol/water not available

Vapour pressure 0,6 mBar

Density and/or relative density 1,1

Relative vapour density not available Particle characteristics not applicable Reason for missing data:substance/mixture is non-soluble (in water)

Temperature: 25 °C

Temperature: 25 °C

#### 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

### **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

The product can react with water generating heat.

#### 10.2. Chemical stability

Stable to normal environment temperatures if used as recommended.

#### 10.3. Possibility of hazardous reactions

The reactions with the following materials can generate heat: alcohol water. Alkali. Amine.

#### 10.4. Conditions to avoid

Do not add water directly to the product. It can cause a violent reaction.

#### 10.5. Incompatible materials

Water, alcohol, amine.

#### 10.6. Hazardous decomposition products

Heating can generate the following products: Gas/Vapors/Toxic fumes of: Dioxide of carbon (CO2). Carbon monoxide (CO). Nitrosis gas (NOX). Hydrogen cyanide (HCN).

### **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Cyanacrililated are not classified as sensitizing according to European legislation and the their rapid polymerization in contact with humidity makes the occurrence of similar unlikely Phenomena, however, ACGIH, American Conference of Governmental Industrial Hygienists,

It reports some sporadic cases of awareness of the skin and respiratory system.

It can cause allergic reactions in predisposed subjects.

#### ΕN



# **Permabond Engineering Adhesives**

# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 8 / 13

### SECTION 11. Toxicological information .../>

Information on likely routes of exposure

Inhalation: irritating to the respiratory tract.

Ingestion: in contact the product can immediately glue the lips together.

Contact with the skin: irritating for the skin. Contact with the product, the skin will stick to itself and to any

Another thing immediately.

Contact with eyes: irritating for the eyes. In contact, the product makes the eyelids join together. His vapors are

tear das

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

**ACUTE TOXICITY** 

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

ethyl 2-cyanoacrylate

LD50 (Dermal): > 2000 mg/kg LD50 (Oral): > 5000 mg/kg

**CHLOROBENZENE** 

LD50 (Oral): > 2000 mg/kg Rat LC50 (Inhalation vapours): 15,5 mg/l/4h Rat

TERT-BUTYL PERBENZOATE

LD50 (Dermal): 2000 mg/kg LD50 (Oral): 2000 mg/kg

#### SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

TERT-BUTYL PERBENZOATE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### E١



# **Permabond Engineering Adhesives**

# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 9 / 13

### SECTION 11. Toxicological information .../>

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### 12.1. Toxicity

Not considered dangerous for the environment.

The mixture is classified on the basis of dangerous information for the ingredients such as defined by the classification criteria for mixtures for each danger class or according to differentiations present in Annex I of 1272/2008/EC. The available information of health/ecological relevant for substances are indicated in section 3 below.

CHLOROBENZENE

LC50 - for Fish 7,72 mg/l/96h Pimephales promelas

TERT-BUTYL PERBENZOATE

 LC50 - for Fish
 1,6 mg/l/96h

 EC50 - for Crustacea
 11 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 0,8 mg/l/72h

 EC10 for Algae / Aquatic Plants
 0,44 mg/l/72h

 Chronic NOEC for Fish
 0,072 mg/l

#### 12.2. Persistence and degradability

CHLOROBENZENE

Solubility in water 100 - 1000 mg/l

NOT rapidly degradable

#### 12.3. Bioaccumulative potential

CHLOROBENZENE

Partition coefficient: n-octanol/water 3

12.4. Mobility in soil

**CHLOROBENZENE** 

Partition coefficient: soil/water 2,42

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available



# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 10 / 13

## **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

08 04 09\* stickers and sealed sealing, containing organic solvents or other dangerous substances.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### **SECTION 14. Transport information**

#### 14.1. UN number or ID number

It applies only to internal containers> 500ml.

ADR / RID: ADR EXEMPT

IMDG: IMDG CODE EXEMPT

IATA: 3334

#### 14.2. UN proper shipping name

ADR / RID: ADR EXEMPT IMDG: IMDG CODE EXEMPT

IATA: AVIATION REGULATED LIQUID, N.O.S.

#### 14.3. Transport hazard class(es)

ADR / RID: ADR EXEMPT

IMDG CODE EXEMPT IMDG:

IATA: Class: 9 Label: 9



#### 14.4. Packing group

ADR / RID: ADR EXEMPT

IMDG CODE EXEMPT IMDG:

IATA: Ш

#### 14.5. Environmental hazards

ADR EXEMPT ADR / RID:

IMDG: IMDG CODE EXEMPT

IATA:

### 14.6. Special precautions for user

ADR / RID: HIN - Kemler: -Limited Quantities: -Tunnel restriction code: -

Special provision: -

IMDG: EMS: -Limited Quantities: -

IATA: Maximum quantity: 450 L Packaging instructions: 964 Cargo: Packaging instructions: 964 Pass.:

Maximum quantity: 450 L

Special provision:

### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

@EPY 11.4.1 - SDS 1004.14

#### E١



## **Permabond Engineering Adhesives**

# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 11 / 13

### **SECTION 15. Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40
Contained substance
Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

Vone

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

### **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Org. Perox C Organic peroxide, type C
Acute Tox. 4 Acute toxicity, category 4
Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

**Skin Sens. 1B** Skin sensitization, category 1B

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H226 Flammable liquid and vapour.
H242 Heating may cause a fire.
H332 Harmful if inhaled.

H319 Causes serious eye irritation.
H315 Causes skin irritation.

H335 May cause respiratory irritation.H317 May cause an allergic skin reaction.

**H400** Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

**EUH202** Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

#### E١



# **Permabond Engineering Adhesives**

# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 12 / 13

#### SECTION 16. Other information .../>>

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the





# Permabond 825

Revision nr.1 Dated 18/01/2023 First compilation Printed on 16/02/2023 Page n. 13 / 13

suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

### CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.