

# Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 10

SDS No.: 364099

V002.5 Revision: 28.05.2018

printing date: 13.12.2018

Replaces version from: 06.04.2018

BONDERITE L-GP 522 ACHESON known as DAG 522

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

BONDERITE L-GP 522 ACHESON known as DAG 522

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Additive for mineral oils and greases

#### 1.3. Details of the supplier of the safety data sheet

Henkel AG & Co. KGaA

Henkelstr. 67

40589 Düsseldorf

Germany

Phone: +49 (211) 797 0 Fax-no.: +49 (211) 798 4008

ua-productsafety.de@henkel.com

## 1.4. Emergency telephone number

The Henkel information service also provides an around-the-clock telephone service on phone no.+49-(0)211-797-3350 for exceptional cases.

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

#### 2.2. Label elements

# Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

**Supplemental information** EUH210 Safety data sheet available on request.

#### 2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### Base substances of preparation:

Pigment Oils

#### Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Distillates (petroleum), hydrotreated heavy	265-157-1	40- 60 %	Asp. Tox. 1 H304
paraffinic, <3% DMSO 64742-54-7	01-2119484627-25		H304

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Immediately wash skin thoroughly with soap and water.

Eve contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Carbon dioxide, foam, powder

Water spray jet

# Extinguishing media which must not be used for safety reasons:

High pressure waterjet

#### 5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

#### 5.3. Advice for firefighters

Wear protective equipment.

### Additional information:

Cool endangered containers with water spray jet.

### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Danger of slipping on spilled product.

#### 6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

#### 6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

#### 6.4. Reference to other sections

See advice in section 8

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid skin and eye contact.

Ensure that workrooms are adequately ventilated.

See advice in section 8

#### Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

#### 7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Do not store near sources of heat or ignition, or reactive materials.

< 28°C

> 8 °C

Store in sealed original container.

#### 7.3. Specific end use(s)

Additive for mineral oils and greases

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Occupational Exposure Limits**

Valid for

Germany

Ingredient [Regulated substance]	ppm	mg/m <sup>3</sup>	,	Short term exposure limit category / Remarks	Regulatory list
Graphite 7782-42-5		10	Exposure limit(s):	2	TRGS 900
Graphite 7782-42-5			*	Category II: substances with a resorptive effect.	TRGS 900
Graphite 7782-42-5		1,25	Exposure limit(s):		TRGS 900

#### **Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Value			Remarks	
		mg/l	ppm	mg/kg	others	
Distillates (petroleum), hydrotreated heavy	oral			9,33 mg/kg		
paraffinic, <3% DMSO						
64742-54-7						

#### **Derived No-Effect Level (DNEL):**

Name on list	Application	Route of	Health Effect	Exposure	Value	Remarks
	Area	Exposure		Time		
Distillates (petroleum), hydrotreated heavy	Workers	inhalation	Long term		5,4 mg/m3	
paraffinic, <3% DMSO			exposure - local			
64742-54-7			effects			

#### **Biological Exposure Indices:**

None

#### 8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

## Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

#### Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >= 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Appearance liquid liquid black

Odor mineral-oil-like

Odour threshold No data available / Not applicable

pH Not applicable

Melting point

No data available / Not applicable
Solidification temperature

No data available / Not applicable
Initial boiling point

No data available / Not applicable
Flash point

Page 200 °C (> 392 °F); no method
Evaporation rate

No data available / Not applicable
Flammability

No data available / Not applicable
Explosive limits

No data available / Not applicable

Vapour pressure No data available / Not applicable Relative vapour density: No data available / Not applicable 1,003 g/cm3

Density

(20 °C (68 °F))

Bulk density No data available / Not applicable Solubility No data available / Not applicable Insoluble

Solubility (qualitative)

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Decomposition temperature 1.000 - 3.000 mPa.s

Viscosity

(Brookfield; Instrument: RVT; 20 °C (68 °F);

speed of rotation: 20 min-1)

Viscosity (kinematic) No data available / Not applicable Explosive properties No data available / Not applicable Oxidising properties No data available / Not applicable

#### 9.2. Other information

No data available / Not applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

Reaction with strong oxidants.

### 10.2. Chemical stability

Stable under recommended storage conditions.

#### 10.3. Possibility of hazardous reactions

See section reactivity

## 10.4. Conditions to avoid

No decomposition if used according to specifications.

#### 10.5. Incompatible materials

See section reactivity.

#### 10.6. Hazardous decomposition products

None if used for intended purpose.

In case of fire toxic gases can be released.

# **SECTION 11: Toxicological information**

#### General toxicological information:

To the best of our knowledge no harmful effects are to be expected if the product is handled and used properly.

#### 11.1. Information on toxicological effects

## Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value	Value	Species	Method
CAS-NO.	type			
Distillates (petroleum),	LD50	> 5.000  mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
hydrotreated heavy				
paraffinic, <3% DMSO				
64742-54-7				

### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Distillates (petroleum),	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
hydrotreated heavy				
paraffinic, <3% DMSO				
64742-54-7				

#### Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Distillates (petroleum),	LC50	5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute
hydrotreated heavy						Inhalation Toxicity)
paraffinic, <3% DMSO						
64742-54-7						

#### Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO 64742-54-7	not irritating	24 h	rabbit	not specified

### Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Distillates (petroleum),	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
hydrotreated heavy				·
paraffinic, <3% DMSO				
64742-54-7				

### Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO 64742-54-7	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

### Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
64742-54-7					

# Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO 64742-54-7	not carcinogenic	dermal	78 w various	mouse	female	OECD Guideline 451 (Carcinogenicity Studies)

paraffinic, <3% DMSO 64742-54-7		various		Studies)
Reproductive toxicity:				
No data available.				
STOT-single exposure:				
No data available.				
STOT-repeated exposu	re::			
No data available.				
Aspiration hazard:				
No data available.				

# **SECTION 12: Ecological information**

#### General ecological information:

Do not empty into drains / surface water / ground water.

#### 12.1. Toxicity

## **Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (petroleum),	LL50	> 100 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish,
hydrotreated heavy paraffinic,					Acute Toxicity Test)
<3% DMSO					-
64742-54-7					

#### Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (petroleum),	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202
hydrotreated heavy paraffinic,					(Daphnia sp. Acute
<3% DMSO					Immobilisation Test)
64742-54-7					

### Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
4 , ,	NOELR	10 mg/l	21 d	1 0	OECD 211 (Daphnia
hydrotreated heavy paraffinic, <3% DMSO					magna, Reproduction Test)
64742-54-7					

### **Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO	EL50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
64742-54-7					
Distillates (petroleum), hydrotreated heavy paraffinic, <3% DMSO 64742-54-7	NOELR	100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

# Toxicity to microorganisms

No data available.

# 12.2. Persistence and degradability

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
Distillates (petroleum),	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready
hydrotreated heavy paraffinic,					Biodegradability: Manometric
<3% DMSO					Respirometry Test)
64742-54-7					

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

Hazardous substances	PBT / vPvB				
CAS-No.					
Distillates (petroleum), hydrotreated heavy	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very				
paraffinic, <3% DMSO	Bioaccumulative (vPvB) criteria.				
64742-54-7					

#### 12.6. Other adverse effects

The product contains hydrocarbons.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you. 130205

# **SECTION 14: Transport information**

#### 14.1. UN number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

## 14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

### 14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0 (2010/75/EU)

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### National regulations/information (Germany):

WGK: WGK = 1, slightly water endangering product. Classification according to the

mixture rules in German VwVwS regulation annex 4 from 27.July 2005

WGK: WGK = 1, slightly water endangering mixture. Classification according to the

mixture rules in German AwSV regulation annex 1, number 5.2 from 18. April

2017.

Storage class according to TRGS 510: 10

### **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows: H304 May be fatal if swallowed and enters airways.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.