

Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 1 / 12

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Permabond CSA LIQUID

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Surface activator

Identified Uses Industrial Professional Consumer
Use -

1.3. Details of the supplier of the safety data sheet

Name Permabond Engineering Adhesives
Full address Niederkasseler Lohweg 18
District and Country 40547 Düsseldorf
Germany

Tel. +44 (0)1962 711 661

e-mail address of the competent person

responsible for the Safety Data Sheet info.europe@permabond.com

Supplier: Permabond Engineering Adhesives Ltd

Wessex Way, Colden Common, Winchester, Hampshire SO21 1WP, UK

tel: +44 (0)1962 711 661

mail: info.europe@permabond.com

1.4. Emergency telephone number

For urgent inquiries refer to +44 (0)1962 711 661 (8.00 am-5.00 pm Mon-Fri)

CHEMTREC UK: +(44)-870-8200418
CHEMTREC Ireland: +(353)-19014670
CHEMTREC Australia: +(61)-290372994
CHEMTREC New Zealand: +(64)-98010034

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure,	H336	May cause drowsiness or dizziness.
category 3		
Hazardous to the aquatic environment, chronic	H411	Toxic to aquatic life with long lasting effects.
toxicity, category 2		



Permabond CSA LIQUID

Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 2 / 12

SECTION 2. Hazards identification

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:









Signal words: Danger

Hazard statements:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing / eye protection / face protection. P301+P310 In case of ingestion: contact an anti -center center or a doctor immediately. In case of contact with the skin: wash abundantly with soap and water. P302+P352 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Contains: HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

TRANS-DICHLOROETHYLENE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

INDEX $60 \le x < 100$ Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336,

Aquatic Chronic 2 H411

EC 927-510-4

CAS

FC

CAS

REACH Reg. 01-2119475515-33-XXXX

TRANS-DICHLOROETHYLENE

INDEX 602-026-00-3 Flam. Liq. 2 H225, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H336, $5 \le x < 10$

Aquatic Chronic 3 H412, Classification note according to Annex VI to the

CLP Regulation: C

STA Inhalation vapours: 11 mg/l

156-60-5 01-2120093504-55-XXXX REACH Reg.

205-860-2

@EPY 11.5.2 - SDS 1004.14



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 3 / 12

SECTION 3. Composition/information on ingredients

N,N-DIMETHYL-p-TOLUIDINA

INDEX 612-056-00-9 $0.1 \le x < 1$

Acute Tox. 3 H301, Acute Tox. 3 H311, Acute Tox. 3 H331, STOT RE 2 H373, Aquatic Chronic 3 H412, Classification note according to Annex VI to the

CLP Regulation: C

EC 202-805-4 STA Oral: 100 mg/kg, STA Dermal: 300 mg/kg, STA Inhalation vapours: 3

mg/l

CAS 99-97-8

REACH Reg. 01-2119956633-31-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames,

E١



Permabond Engineering Adhesives

Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 4 / 12

SECTION 6. Accidental release measures/>

sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

Storage class TRGS 510 (Germany):

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU Deutschland Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und

Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung

gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56

DNK Danmark Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019

FIN Suomi HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH

HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 5 / 12

SECTION 8. Exposure controls/personal protection

			N,N-DIMETH	IYL-p-TOLUID	INA				
Predicted no-effect cor	ncentration	- PNEC							
Normal value in fresh	water					0,153	mg/l		
Normal value in marine water					0,015	mg/l			
Normal value for fres	h water sedi	ment				45,38	mg/kg		
Normal value for marine water sediment						45,38	mg/kg		
Normal value for water	er, intermitte	nt release				0,153	mg/l		
Normal value for the	terrestrial co	mpartment				18,68	mg/kg		
Health - Derived no-eff	ect level - D	NEL / DMEL							
	Effects on consumers				Effects on workers				
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic	
	local	systemic	local	systemic	local	systemic	local	systemic	
Inhalation				1.352					
				mg/m3					
Skin				1.186					
				mg/kg/d					

				TRANS-DICHL	OROETHYLE	NE			
Threshold Limit Va	lue								
Type	Country	ry TWA/8h		STEL/15r	STEL/15min		bservations		
		mg/m3	ppm	mg/m3	ppm				
AGW	DEU	800	200	1600	400				
TLV	DNK	790	200	1580	400				
HTP	FIN	800	200	1000	250				
Predicted no-effect	t concentra	tion - PNEC	;						
Normal value in f	resh water						0,0364	mg/l	
Normal value in r	marine wate	r					0,0036	mg/l	
Normal value for	fresh water	sediment					0,548	mg/kg/d	
Normal value for	marine water	er sediment					0,0548	mg/kg/d	
Normal value of S	STP microoi	rganisms					17	mg/l	
Normal value for the terrestrial compartment					0,0563	mg/kg/d			
Health - Derived no	-effect leve	el - DNEL / I	DMEL						
	Effec	ts on consu	mers			Effects on workers			
Route of exposur	re Acut	e Acu	ıte	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	sys	temic	local	systemic	local	systemic	local	systemic
Oral		•			57		•		•
					mg/kg bw/d				
Inhalation					198				797
					mg/m3				mg/m3

		HYDROCARB	BONS, C7, N-AL	KANES, ISOAL	KANES, CYC	CLICS		
Health - Derived no-eff	ect level - D	NEL / DMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Oral				149				
				mg/kg bw/d				
Inhalation				447				2085
				mg/m3				mg/m3
Skin				149				300
				mg/kg bw/d				mg/kg
								hw/d

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low

hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 6 / 12

SECTION 8. Exposure controls/personal protection/

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion. EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a type AX filter, whose limit of use will be defined by the manufacturer (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Value Appearance liquid Colour green characteristic Odour Melting point / freezing point not available Initial boiling point 45 °C. Flammability not available Lower explosive limit not available Upper explosive limit not available Flash point Λ °C. Auto-ignition temperature not available Decomposition temperature not available not available not available Kinematic viscosity Solubility not available Partition coefficient: n-octanol/water not available not available Vapour pressure Density and/or relative density 0.7 Relative vapour density not available Particle characteristics not applicable

Information

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

E١



Permabond Engineering Adhesives

Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 7 / 12

SECTION 10. Stability and reactivity .../>>

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: >2000 mg/kg

N,N-DIMETHYL-p-TOLUIDINA

LD50 (Dermal): > 2000 mg/kg

STA (Dermal): 300 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 1767 mg/kg

STA (Oral): 100 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LC50 (Inhalation vapours): 1,4 mg/l/4

STA (Inhalation vapours): 3 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

TRANS-DICHLOROETHYLENE

 LD50 (Dermal):
 > 5000 mg/kg

 LD50 (Oral):
 7902 mg/kg

 LC50 (Inhalation vapours):
 24100 ppm/4h

STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 8 / 12

SECTION 11. Toxicological information .../>>

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS LD50 (Dermal): 3000 mg/kg LD50 (Oral): > 8 mg/kg LC50 (Inhalation vapours): > 23,3 mg/l/4h

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and is toxic for aquatic organisms. In the long term, it have negative effects on acquatic environment.

12.1. Toxicity

N,N-DIMETHYL-p-TOLUIDINA

LC50 - for Fish 52 mg/l/96h

TRANS-DICHLOROETHYLENE

LC50 - for Fish 135 mg/l/96h EC50 - for Crustacea 250 mg/l/48h

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS

 LC50 - for Fish
 > 13,4 mg/l/96h

 EC50 - for Crustacea
 3 mg/l/48h

 EC50 - for Algae / Aquatic Plants
 20 mg/l/72h

12.2. Persistence and degradability



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 9 / 12

SECTION 12. Ecological information .../>>

TRANS-DICHLOROETHYLENE NOT rapidly degradable

HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1993

14.2. UN proper shipping name

ADR / RID: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS;

TRANS-DICHLOROETHYLENE)

IMDG: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS;

TRANS-DICHLOROETHYLENE)

IATA: FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS;

TRANS-DICHLOROETHYLENE)



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 10 / 12

SECTION 14. Transport information .../>>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO IMDG: NO IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 33 Limited Quantities: 1 L Tunnel restriction code: (D/E)

Special provision: 274, 601, 640(C-D)

IMDG: EMS: F-E, <u>S-E</u> Limited Quantities: 1 L

IATA: Cargo: Maximum quantity: 60 L Packaging instructions: 364
Passengers: Maximum quantity: 5 L Packaging instructions: 353

Special provision: A3

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c-E2

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 11 / 12

SECTION 15. Regulatory information

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 2: Hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flammable liquid, category 2 Flam. Lig. 2 Acute Tox. 3 Acute toxicity, category 3 Acute Tox. 4 Acute toxicity, category 4 Asp. Tox. 1 Aspiration hazard, category 1

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2 Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3 **Aquatic Chronic 2** Hazardous to the aquatic environment, chronic toxicity, category 2 **Aquatic Chronic 3** Hazardous to the aquatic environment, chronic toxicity, category 3

Highly flammable liquid and vapour. H225

H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled.

H332 Harmful if inhaled

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

I FGFND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).



Permabond CSA LIQUID

Revision nr.1 Dated 02/10/2023 First compilation Printed on 02/10/2023 Page n. 12 / 12

SECTION 16. Other information .../>>

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.